



22743 Freeport Road  
Sterling, IL 61081

## Tractor Grill Installation Instructions

Rev 110110

**Applies to the following items: G-856, G-1206, G-826, G-756, G-W856, G-2706**

1. Carefully remove grill decal from tractor. Trim out logo. This will be reapplied after new grill is installed.
2. Using a Sharpie® pen, other black marker or paint, color the grill area on the tractor black.
3. Carefully remove the desired grill from the sprue.
4. Apply a small amount of cyanoacrylate adhesive (CA or super glue) to the tractor front in each corner. Carefully place grill on tractor.
5. Reinstall logo to the front of the grill.

### Special Notes:

1. If installing the G-2706 industrial grill, the grill must first be painted. Paint yellow. Background behind lettering is black. When black is dry, highlight lettering carefully with white using the drybrushing technique.
2. If using any of the grills with headlight openings, determine what you are going to do for headlights. Headlights are not included in the kit. We recommend using MV products P/N 22 lense, available from [www.discountmodels.com/m.v.\\_lenses.shtml](http://www.discountmodels.com/m.v._lenses.shtml) or [www.Walthers.com](http://www.Walthers.com) (Walthers P/N 516-22). The holes for these lenses should be drilled first before any other work is done. Position grill on tractor and use it to mark the hole centers. As an alternative, the area behind the light openings could simply be painted silver.